Safety Data Sheet			- 14
Fly Ash (All Types)			
Version 2.0			ECOMAIERIAL technologies
Date Prepared: 06/27/2023			
SECTION 1: IDENTIFICA	TION		
1.1 Product Identifier	h Class C fluench Class E fluench Da	admin and blands of Class C and	Efficient OITE Intriv D2
Performance Pozzola	sh, Class C fly ash, Class F fly ash, Ro n, Economizer Ash, Bottom Ash, PV2 -Stone, Celceram, Powerlite		-
1.2 Intended Use of th	e Product		
	bard, concrete, asphalt, roofing mat for various civil engineering application		nctional filler and
	d Telephone Number of the Res		
Company	·	. ,	
Eco Material Technol	ogies Inc., and its subsidiary and aff	iliate companies	
10701 S. River Front	-		
South Jordan, UT 840	95		
(801) 984-9400			
1.4 Emergency Telepho	one Number		
502-525-3561			
SECTION 2: HAZARD(S) I	DENTIFICATION		
2.1 Classification of the	Substance or Mixture (GHS-US)		
Skin Irritation 2			
Eye Irritation 2A			
STOT-SE (Single Exposure)			
STOT-RE (Repeated Exposu	re) 1 (Respiratory)		
Carcinogenicity 1A			
2.2 Label Elements	A		
Hazard Pictograms:			
Signal Word:	• Danger		
Hazard Statements:	Causes skin irritation. (H3)	15)	
	Causes serious eye irritati	on. (H319)	
	 May cause respiratory irri 	tation. (H335)	
	• May cause cancer (H350)	-	
	 Causes respiratory harm t 	hrough prolonged or repeated e	exposure. (H372)

Precautionary	 Do not handle until all safety precautions have been read and understood. (P202)
Statements:	• Avoid breathing dust. (P261)
	 Wash hands, forearms, and other exposed areas thoroughly after handling. (P264)
	 Wear protective gloves, protective clothing, and eye protection. (P280)
	 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301) (P330) (P331)
	 IF ON SKIN (OR HAIR): Remove all contaminated clothing immediately. Rinse skin with water/shower. (P303) (P353) (P361)
	• IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. (P304) (P340)
	 IF IN EYES: Rinse cautiously with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing until pain or irritation subsides. (P305) (P338) (P351)
	 If symptoms persist: Get medical advice/attention. (P308) (P313)
	 Remove contaminated clothing and wash before re-use. (P362) (P364)

2.3 Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Repeat inhalation exposuremay cause obstructive pulmonary disease, chronic bronchitis, silicosis, and cancer.

2.4 California Proposition 65:



WARNING: CANCER—www.P65Warnings.ca.gov

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Description of Product

Fly Ash—All Types

3.2 Mixture Ingredients and Hazard Classification

Ingredient	Product Identifier (CAS No.)	% (w/w)	Hazard Classification (GHS-US)
Fly ash combustion residue (amorphous calcium-aluminum silicates)*	68131-74-8	70 – 90	 Skin Irritation 2, H315 Eye Irritation 2A, H319 STOT-SE (Single Exposure) 3 (Respiratory), H332 STOT-RE (Repeated Exposure) 1 (Respiratory), H373
Crystalline silica	14808-60-7	< 16 < 2.1 (respirable fraction)	 STOT-RE (Repeated Exposure) 1 (Respiratory), H373 Carcinogenicity 1 (H350)
Calcium oxide	1305-78-8	< 30	Skin Irritation 2, H315Eye Irritation 1, H320
Potassium oxide	12136-45-7	1-5	Skin Irritation 2, H315Eye Irritation 2A, H319
Phosphorus pentoxide	1314-56-3	< 2	 Skin Corrosivity 1, H313 Eye Irritation 1, H319

*Fly ash and other CCPs are UVCB substances (substance of unknown or variable composition or biological). Fly ash is defined by the U.S. EPA as: "The residuum from the burning of a combination of carbonaceous materials. The following elements may be present as oxides: aluminum, calcium, iron, magnesium, nickel, phosphorus, potassium, silicon, sulfur, titanium, and vanadium." The exact composition of fly ash is dependent on the fuel source and flue additives composed of many constituents. The classification of the final substance is dependent on the presence of specific identified oxides as well as other trace elements.

SECTION 4: FIRST AID MEASURES

4.1 Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. Any person who is experiencing symptoms of injury or illness should be moved to a comfortable area with fresh air, and the label or SDS of this material reviewed. If feeling unwell, seek medical advice.

Inhalation: Move person to fresh air. Provide drinking water, if conscious, to flush mouth and irrigate upper respiratory tract. Seek medical attention if pain, coughing or other symptoms do not subside.

Eye Contact: If the exposed person experiences burning eye irritation due to dust exposure, careful flushing with clean water should continue for at least 15 minutes. If contact lenses are present, they should be removed after flushing if easy to do. Continue flushing. Obtain medical attention if irritation persists.

Skin: Flush skin with plenty of water until irritation subsides. If irritation persists, obtain medical assistance. Wash contaminated clothing before re-use.

Ingestion: Ingestion of this material is not an expected route of exposure. Rinsing mouth with water is appropriate.

4.2 Most Important Symptoms and Effects—Both Acute and Delayed

General: The most important symptoms and effects from exposure to this material after contact with dust are eye and skin irritation. Breathing dust can cause respiratory irritation and respiratory system chronic illness if significant exposures occur repeatedly.

Inhalation: The immediate acute response to dust inhalation is respiratory system irritation. Upon repeated dust exposure at levels exceeding regulatory limits, crystalline silica content of the dust may cause delayed or chronic respiratory illnesses, including silicosis and cancer.

Eye Contact: Exposures of the eyes to dust may result in irritation, which must be treated immediately with first aid (Section 4) followed by medical attention if irritation persists.

Skin Contact: Skin contact can cause irritation.

4.3 Indication of Immediate Medical Attention and Special Treatment

Any time symptoms of eye or respiratory irritation occur, immediate first aid should be provided as described in Section 4.1, and medical attention should be obtained if irritation persists.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Material is notcombustible.

5.2 Special Hazards Arising from the Substance or Mixture

Fire Hazard: Not combustible.

Explosion Hazard: Material is not explosive. **Reactivity:** Material is not reactive.

5.3 Advice for Firefighters

Not applicable.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment, and Emergency Procedures

General Measures: Do not breathe dust. Do not get dust in eyes or on skin.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip responders and clean-up personnel with proper protection, including appropriate clothing, eye and face protection. Respiratory protection should be used as necessary to prevent dust exposure.

Emergency Procedures: Ventilate area if dust is generated.

6.2 Environmental Precautions

Reuse material as appropriate to avoid disposal.

6.3 Methods and Material for Containment and Clean-Up

Containment: Contain and collect as any solid. Avoid actions that cause dust to become airborne. Do not breathe dust, and do not allow large quantities of dust or wetted material to contact skin or eyes.

See Section 8. Exposure Controls and Personal Protection. For waste management information, refer to Section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Additional Hazards when Processed: Dust will be generated when transferring this material. Use engineered controls and other practices to control dust. Personal Protective Equipment (PPE) described in Section 8 should beused as necessary.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking, and again when leaving work.

7.2 Conditions for Safe Storage, Including any Incompatibilities

Not applicable.

7.3 Specific End-Use(s)

No applicable limits.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limits

The following exposure limits are based on a time-weighted full-shift exposure, unless otherwise noted.

Ingredient	OSHA PEL ⁽¹⁾	ACGIH-TLV ⁽²⁾	Other
Fly ash combustion residues ⁽³⁾ (amorphous calcium-aluminum silicates)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³ (total) 3 mg/m ³ (respirable)	
Crystalline silica ⁽³⁾ (respirable fraction)	50 μg/m³ (respirable)	0.025 mg/m ³ (respirable)	0.05 mg/m ³ (respirable) ⁽⁴⁾
Calcium oxide	5 mg/m ³ (total)	2 mg/m ³ (total)	2 mg/m ³ (total) ⁽⁴⁾

Ingredient	OSHA PEL ⁽¹⁾	ACGIH-TLV ⁽²⁾	Other
Potassium oxide	2 mg/m ³ (total, ceiling)	2 mg/m ³ (total)	2 mg/m ³ (total, ceiling) ⁽⁴⁾
Phosphorus pentoxide	None Established	None Established	

fn(¹⁾ OSHA PEL (Permissible Exposure Level) at 29 CFR 1910.1000)

 $fn^{(2)}$ ACGIH-TLV (American Conference of Governmental Industrial Hygienists-Threshold Limit Values 2018)

 $fn^{(3)}$ Crystalline silica is regulated by OSHA as Respirable Crystalline Silica (RCS) [29 CFR 1910.1053]. The amount of RCS in fly ashhas been determined to be less than 4%.

 $fn^{(4)}$ NIOSH REL (National Institute for Occupational Safety and Health Recommended Exposure Limit)

8.2 Exposure Controls

Appropriate Engineering Controls: Emergency eyewash equipment should be available in the immediate vicinity of any potential exposure. Use local exhaust or other suppression methods to maintain dust levels below exposure limits. **Personal Protective Equipment:** Protective goggles or safety glasses, gloves, protective clothing. Wear respiratory protection if dust is present when transferring or processing.



Hand Protection: Protective gloves as appropriate to prevent irritation and other hand injuries.

Eye and/or Face Protection: Approved safety glasses, goggles, and/or face-shield.

Skin and Body Protection: Appropriate work clothing and footwear should be worn.

Respiratory Protection: If exposure limits may be exceeded or irritation is experienced, approved respiratoryprotection should be worn in accordance with OSHA Respiratory Protection Standard [29 CFR 1910.134].

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties			
Physical State: Granular solid.	Lower Flammable Limit: Not applicable.Upper		
Appearance: Flowable material—Various colors (gray totan)	Flammable Limit: Not applicable. Vapor		
Odor: Essentially odorless.	Pressure: Not applicable.		
Odor Threshold: Not applicable.	Relative Vapor Density at 20° C: Not applicable.		
pH: < 11 (in water)	Relative Density: Not applicable. Specific		
vaporation Rate: Not applicable. Gravity: 2.2 – 2.8 Solubility: Slightly			
Melting Point: Not applicable.	soluble in water.		
Freezing Point: Not applicable.	Partition Coefficient—N-Octanol/Water: Notapplicable.		
Boiling Point: Not applicable.	Viscosity: Not applicable.		
Flashpoint: Not applicable.	Explosion Data—Sensitivity to Mechanical Impact:		
Auto-Ignition Temperature: Not applicable.	Not applicable.		
Decomposition Temperature: Not applicable.	Explosion Data—Sensitivity to Static Discharge: Not		
Flammability (solid, gas): Not applicable.	applicable.		

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Hazardous reactions are not expected to occur under normal conditions.

10.2 Chemical Stability

Stable.

10.3 Possibility of Hazardous Reactions

Hazardous polymerization or other reactions are not expected. For gas generation, see 10.6.

10.4 Conditions to Avoid

Material can become airborne in moderate winds. Dry material should be stored in silos or other structures.Material stored outdoors should be covered or dampened to reduce dusting.

10.5 Incompatible Materials

Not applicable.

10.6 Hazardous Decomposition Products

Not expected under normal conditions. Wetted material, which contains ammonia, may release ammonia gas, whichmay result in nuisance odor or potential harmful exposure in a confined area.

SECTION 11: TOXCOLOGICAL INFORMATION

11.1 Likely Routes of Exposure

Skin Contact: Material may irritate unprotected skin.

Eye Contact: Material may cause serious irritation of unprotected eyes.

Inhalation: Respirable dust may be generated that if inhaled, can cause respiratory system irritation. Prolonged orrepeated inhalation exposure may cause chronic respiratory illness, including silicosis and cancer.

Ingestion: Not expected to be an exposure route of concern.

11.2 Symptoms Related to Physical, Chemical, and Toxicological Characteristics

Immediate Effects: Irritation of skin, eyes, and respiratory tract due to dust inhalation or exposure of eyes and skinto material.

Delayed and Chronic Effects: Inhalation of dust on a prolonged or repeated basis may result in chronic lung disease or silicosis, and may also result in lung cancer.

11.3 Numerical Measures of Toxicity

The acute and chronic effects of exposure to this product's dust have not been quantified.

11.4 Carcinogenicity

The ingredient quartz, also known as crystalline silica, has been determined to be carcinogenic by the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP). The potential cancer (H350) Hazard Class designation disclosed in Section 2 is conservative and based on the percentage of crystalline silica in this mixture product. Toxicological studies conducted on fly ash materials, including oral and inhalation repeated dose, as well as mutagenicity have shown no evidence of carcinogenic effects that, except for numerical percentage of crystalline silica and other potential carcinogenic substances included in OSHA GHHCS Guidance, classification as acarcinogen is not required. Reference: *American Coal Ash Association Safety Data Sheet Guidance Document*, May 2015.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

No additional information available.

12.2 Persistence and Degradability

Not available.

12.3 Bioaccumulative Potential

Not available.

12.4 Mobility in Soil

Not available.

12.5 Other Adverse Effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal Recommendations: Excess material should be re-used or recycled. Material as a waste is not a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) (40 CFR 261), but waste material should be prevented from entering sewer systems, surface waters or the environment. Dispose of waste material in accordance with all local, regional, national, provincial, territorial, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 DOT (U.S.)

Not regulated for transport. 14.2 IMDG (Maritime Code)

14.2 INDO (INALICITIE

Not for transport. 14.3 IATA

14.5 IATA

Not regulated for transport.

14.4 TDG (Canada)

Not regulated for transport.

SECTION 15: REGULATORY INFORMATION					
	15.1 U.S. Federal Regulations				
	SARA Section 311/312 Hazard Classes (40 CFR 370)				
	Reporting of fly ash is required if reporting threshold (10,000 pounds) is exceeded				
	Skin corrosion or irritation				
	 Serious eye damage or irritation 				
•	 Specific target organ toxicity (single or repeated exposure)—Respiratory 				
SARA Section 313 Emission Reporting					
Fly ash is not a chemical listed at Part 372.65 Trace elements should be considered in TRI reporting.					
TSCA Inve	-				
All constit	cuents are included on the To	oxic Substances Control Ac	ct Chemical Inventory (40 CFR 7	20) and exempt from	
inventory	update reporting (40 CFR 71	.0).			
15.2 U.S.	State Regulations				
State Righ	nt-to-Know Laws				
Fly as	sh contains hazardous substa	nces subject to inventory	reporting and other requireme	ents of the	
Mass	achusetts, New Jersey, Penns	sylvania and Rhode Island	l right-to-know laws.		
	Component	CAS No.	Component	CAS No.	
	Calcium oxide	1305-78-8	Phosphorus pentoxide	1314-56-3	
			(or phosphorus oxide)		
	Potassium oxide	12136-45-7			
	Silica – crystalline quartz	14808-60-7			
	<u>References to Table</u> :				
	Massachusetts: 301 CM	MR 41, et seq. (January 16, 2	015)		
	New Jersey: New Je	ersey Revised Statutes 34:5A	-5 (2016) and New Jersey Health D	Department List	
	Pennsylvania: Title 34	4 Pennsylvania Code, Chapte	er 323		
	Rhode Island: Rhode	Island General Laws Title 28	3, Chap. 21-3 List of Chemicals		
	-		rences to other regulatory lists; fo	r example, EPCRA § 313 and	
	OSHA PELs at 29 CFR 1910.100				
California	Proposition 65—Warning R	equired			
Refer	to Section 2.4.				
15.3 Cana	idian WHMIS Regulations				
Crystalline	e silica, titanium dioxide and	other fly ash constituents	are hazardous materials and s	ubject to WHMIS	
2015.		i.			
15.4 Othe	er: HMIS and NFPA				
HMIS:			NFPA:		
HEALTH ¥ 2					
				\mathbf{N}	
PHYSICAL HAZARD 0					
			\sim		
	PROTECTION:	staativa alathing and	×		
-	oggles or safety glasses, gloves, pro ootwear. Wear respiratory protecti	_			
p. c. c. i. c. i.					
·					

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Party Responsible for Preparation of this Document

Eco Material Technologies Inc., and its subsidiary and affiliate companies (801) 984-9400

Limitations

The information and recommendations set forth herein are based on data we have in our possession, and we have reason to believe is accurate. It is, however, the user's responsibility to determine the safety, toxicity, or suitabilityfor his/her own use of the herein described product. Because the actions of others are beyond our control, Eco Material Technologies Inc., and its subsidiary and affiliate companies makes no warranty expressed or implied regarding accuracy of the data or the results to be obtainedfrom the use thereof.

NA GHS SDS